

# MHS 409

## Remote light indicator

Remote light indicator MHS 409 is an element of Fire Detection and Fire Alarm System, which is used as parallel signalling of fire from one or more detectors connected to a line (loop).



It is intended for connecting to all types of addressable and conventional (non-addressable) smoke detectors LITES.

### Technical parameters

Power supply	6 – 8 V <sub>imp</sub> (addressable and conventional voltage detectors) 6 – 24 V <sub>imp</sub> (conventional current detectors)
Current consumption	max. 30 mA
Cross-section of connectable wires	0,2 – 2,5 mm <sup>2</sup>
Protection according to ČSN EN 60592	IP 40
Radio screening degree	B-class equipment according to ČSN EN 55022
Dimensions	80 x 80 x 37 mm
Weight	cc 0,1 kg

Product is intended for operation with safe equipment in sense of ČSN EN 60950.

### Working conditions

The MHS 409 is intended for the interior of objects without occurrence of aggressive substances, and for places where its protection and climatic immunity conform, and where sudden temperature changes leading to dew and ice accretion don't occur.

Working temperature range	-25°C ÷ +70°C
Relative humidity	max. 95% at +40°C
Atmospheric pressure	66 ÷ 106 kPa
Operational position	arbitrary (according to design)

Version 04/2017